



OUTLANDER™ 800R

XT model shown.



OUTLANDER 800R



OUTLANDER 800R XT™

SPECIFICATIONS

ENGINE

Type	799.9cc, V-twin, liquid-cooled, SOHC, 8-valve (4-valve/cyl)
Bore & Stroke	91 x 62 mm
EFI System/Carburetor	46 mm Throttle Body, 2 Siemens™ VDO injectors
Starting System	Electric
Transmission	CVT, sub-transmission with high, low, park, neutral & reverse. Standard engine braking
Drive Train	Selectable 2w/4w shaft driven with Visco-Lok† front differential

CHASSIS

Frame	SST G2
Front Suspension Type/Shocks	Double A-arm
Front Suspension Travel	9 in (229 mm)
Rear Suspension Type/Shocks	Torsional Trailing arm Independent (TTI)
Rear Suspension Travel	9.3 in (236 mm)
Front Brake	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear Brake	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper
Tires/Front	26 x 8 x 12 in 660 x 203 x 305 mm
Tires/Rear	26 x 10 x 12 in 660 x 254 x 305 mm
Wheels	Cast-aluminum

DIMENSIONS

L x W x H (in)	86 x 46 x 44 in
L x W x H (mm)	2,184 x 1,168 x 1,118 mm
Wheelbase	51 in (1,295 mm)
Seat Height	34.5 in (877 mm)
Ground Clearance	12 in (305 mm)
Dry Weight	729 lb (331 kg)
Towing Capacity	1,300 lb (590 kg)
Rack Capacity	Front: 100 lb (45 kg) Rear: 200 lb (90 kg)
Storage	Rear: 5.7 US gal (21.4L)
Fuel Capacity	5.4 US gal (20.5L)

FEATURES

Instrumentation	Multi-function digital LCD gauge: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock, auto shut off after 15 minutes
Anti-theft System	D.E.S.S.™ (Digital Encoded Security System)
Electrical	Prewired for winch
Lighting	230-watt from twin 60-watt projectors and dual 55-watt reflectors with tail light/brake light
DC Outlet	Lighter type in console, standard connector in the back (15A)
Color Available	Viper Red ■

WARRANTY

Basic	6 months limited factory warranty
Extended	B.E.S.T. available from 12 to 36 months

XT PACKAGE

- Tri-mode Dynamic Power Steering (DPS™)
- Visco-Lok QE
- Cast-aluminum wheel with machined finish
- 26-inch Carlisle™ ACT radial tires
- 3000-pound WARN™ winch with roller fairlead, wired remote control & integrated remote storage
- Heavy-duty front & rear bumpers
- Handlebar with wind deflectors
- 650-watt magneto
- Industry-exclusive NEXT G-1 Vista™ Camo color option
- NEW Pure Magnesium Metallic painted plastics color option
- Colors: Black
 Yellow
 Camo
 Pure Magnesium Metallic